

		Key features	
		High quality imaging with 3K, 2960 × 1665 resolution 2.8 mm fixed focal lens Up to 40 m white light and 40 m IR distance for bright night imaging Smart-Hybrid Light, optimize your security with flexible lighting options High quality audio with audio over coaxial cable, built-in mic, and built-in speaker Provide real-time communication via built-in two-way audio Water and dust resistant (IP67)	
Model Number		T259B-HT	
Analog HD Camera			
Camera	Image sensor	3K CMOS	
	Video Resolution	2960 (H) × 1665 (V)	
	Signal System	PAL/NTSC	
	Frame Rate	TVI: 3K @10 fps/12.5 fps/20 fps/25 fps, 4 MP @25 fps/30 fps, 1080P @25 fps/30 fps	
	Lens	2.8mm	
	Min.Illumination	0.01 Lux @ (F1.6 AGC ON), 0 Lux with IR	
	Angle of View	Horizontal FOV: 112°, vertical FOV: 62°, diagonal FOV: 131°	
	Supplement Light type	Smart,IR,White Light	
	Supplement Light Range	IR : Up to 40 m, white Light : Up to 40 m	
	Day/Night Mode	Auto/Color	
	Wide Dynamic Range	Digital WDR	
	Image Enhancement	DWDR,BLC,HLC,Global,HLS	
	White Balance	Auto/Manual	
	AGC	Yes	
	Built-in Microphone	Yes	
	Built-in speaker	Yes	
	Video Output	BNC, switchable TVI/AHD/CVI/CVBS	
General	Housing	Main body: Metal; Enclosure: Plastic	
	Color	Black	
	Operating Power	12 VDC ± 25%	
	Consumption	Max. 6.4 W	
	Operating Temperature	-40 °F – 140 °F /-40 °C – 60 °C	
	Indoor/Outdoor	Indoor/Outdoor	
	Weatherproof Rating	IP67	

	Dimension (L x W x H)	110 mm × Ø 102.7 mm (4.33" × Ø 4.04")
	Weight	Approx. 370 g (0.81 lb.)























































































































