


| | | |
|---|--------------------------|---|
|  | | Key features High quality imaging with 4K, 3840 × 2160 resolution 2.8 mm, fixed focal lens Up to 40 m white light and 40 m IR distance for bright night imaging Smart-Hybrid Light, optimize your security with flexible lighting options High quality audio with audio over coaxial cable, built-in mic, and built-in speaker Provide real-time communication via built-in two-way audio Water and dust resistant (IP67) |
| Model Number | | T289W-HT |
| Camera | Image Sensor | 4K CMOS |
| Camera | Max. Resolution | 3840 (H) × 2160 (V) |
| | Shutter Time | PAL: 1/12.5 s to 1/50,000 s,NTSC: 1/15 s to 1/50,000 s |
| | Min. Illumination | 0.01 Lux @(F1.6, AGC ON), 0 Lux with White Light |
| | Day & Night | ICR |
| | Angle Adjustment | Pan: 0° to 360°, tilt: 0° to 75°, rotate: 0° to 360° |
| | Signal System | PAL/NTSC |
| Lens | Lens Type | 2.8 mm, fixed lens |
| | Focal Length & FOV | 2.8 mm, horizontal FOV: 105°, vertical FOV: 62°, diagonal FOV: 134°; |
| | Lens Mount | M12 |
| Microphone | Pickup Distance | In a radius of up to 5 m |
| | Amount | 1 |
| Speaker | Rated Power | 2 W |
| | Speaker Range | In a radius of up to 5 m |
| Illuminator | Supplement Light Type | Smart, IR, White Light |
| | Supplement Light Range | IR: Up to 40 m, White Light: Up to 40 m |
| Image | Image Settings | Anti-banding, Brightness, Sharpness, Smart IR |
| | Frame Rate | TVI: 8 MP @12.5 fps/15 fps, 3K@20 fps/25 fps, 4 MP@25 fps/30 fps, 1080p@25 fps/30 fps |
| | Day/Night Mode | Auto/Color |
| | Wide Dynamic Range (WDR) | Digital WDR |
| | Image Enhancement | DWDR, BLC, HLC, Global |
| | Noise Reduction | 2D DNR |
| | White Balance | Auto, Manual |
| Audio | Audio Function | Echo Cancellation, AI Noise Reduction, Automatic Gain Control |
| Interface | Video Output | 1 HD analog output |
| General | Power | 12 VDC ± 25%, max. 6.8 W |
| | Material | Main body: Metal; Enclosure: Plastic |
| | Dimension | Ø110 mm × 102.7 mm (Ø4.33" × 4.04") |
| | Weight | Approx. 375 g (0.81 lb.) |
| | Operating Condition | -40 °C to 60 °C (-40 °F to 140 °F). Humidity 90% or less (non-condensing) |

| | | |
|--|------------|------|
| | Protection | IP67 |
|--|------------|------|